

info@debyetechnic.com

www.debyetechnic.com

Debye Technic Ar-Ge Mühendislik Danışmanlık Ltd.Şti

CALORIMETER IC 210



CALORIMETER IC 210

Semi-automated, compact and light-weighted calorimeter with water circulator. To determine calorific value of solid and liquid samples.

For commercial, industrial and educational usages.













INCLUDED COMPONENTS

- Power Pack (Cables and Power Supply)
- Decompostion Vessel (Bomb)
- Water Circulator (With Cooling and Heating Properties)
- Integrated Screen or PC Controller (Optional)
- Software
- O-ring Set
- Tool Kit
- Oxygen Regulator
- Sample Preperation Unit
- Crucible Compartment
- Benzoic Acid
- Ignition Wire
- Crucible

| IC210 General Technical Data | Information |
|--|--|
| Temperature Measurement Resollution | 0.0001 K |
| Measuring Mode | Isoperibol |
| Water Filling and Draining | Automatic |
| Ignition | Automatic |
| Analysis Duration | < 16 min. |
| Preperation Time for Operator | maximum 2 min. |
| Range of Measurement | 40 000 J |
| Reproducibility | RSD <0,05% |
| Operating Oxygen Pressure | 30-40 bar |
| Imput Power Max. | 200 W |
| Rated Voltage | 220V / 5A |
| Dimensions | 498x678x396 mm |
| Protection Class | III |
| Ambient Temperature | 15-35 °C |
| Ambient Temperature Ambient Humidity | |
| | < 85% |
| Frequency | 50/60 Hz. IP 10 |
| Protection Class According to DIN | |
| Cooling Medium | Water Circulator |
| Water Filter | Included |
| Oxygen Filling | Manuel |
| Degasification | Manuel |
| Halogen (Decomposition) Vessel Analysis According to | Optional ISO 1928 |
| | ISO 18125 ISO 9831 ISO 1716 ASTM D5865 ASTM D5468 ASTM D4809 ASTM E711 DIN 51 900 |
| Interface | USB |
| | |
| Languages | EN/TR |
| | |
| Water Circulator | Information |
| Water Circulator Operating Options | Information Heating/Cooling |
| Water Circulator Operating Options Temperature Range | Information Heating/Cooling -20 / 100 °C |
| Water Circulator Operating Options Temperature Range Bath Capacity | Information Heating/Cooling -20 / 100 °C 7 L |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy | Information Heating/Cooling -20/100°C 7 L ±0,03 |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis According to: Username Analysis Name |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis Listing | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis According to: Username Analysis Date |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis Listing Recalculation on Previous Analysis | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis According to: Username Analysis Name Analysis Date Yes |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis Listing Recalculation on Previous Analysis | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis According to: Username Analysis Date |
| Water Circulator Operating Options Temperature Range Bath Capacity Temperature Stabilitiy Heating Capacity Cooling Capacity Power Requirements Dimensions Software Choosing Analysis Type Operating on Sofware While Analysis Continues During Analysis Graphic Progress Analysis Graphic Output Calculation Excel Output Analysis Control File Encryption User Registiration After Analysis Listing Recalculation on Previous Analysis Servie Authorisation User Friendly Service Feedbacks | Information Heating/Cooling -20 / 100 °C 7 L ±0,03 1,1 kW 0,25 kW 220-240 V / 50-60 Hz 292x423x620 mm Information Calibration/Standart Yes Yes ±0,03 Gross/ Net Calorific Value Yes Device Control/ Analysis Simulation Yes Unlimited List and Review Analysis According to: Username Analysis Name Analysis Date Yes Full Authorisation |


ABOUT CALORIMETER IC 210

IC210 semi-automatic calorimeter provides fast and accurate calorific data for a wide range of samples.

For high precision and ease of use, our design combined with our special software technology.

Improved instrument with all water filling and draining as well as heating and cooling of the water are controlled automatically.

Easy to operate software with simple interface, semi-automized analysis control, data and graphic viewing and exporting, user-defined settings and simplied data handling. Simple usage makes it easy for everyone to operate and understand.



Calorimeter-PC Software



Spare Parts and Consumables

